

M E S C

Middle East Specialized Cables

PROCESS FIELDBUS (PROFIBUS) DP STANDARD CABLE IEC 61158-2 TYPE A RS 485 300 V 75°C



Application:

Fieldbus cable for Profibus DP and FIP according to IEC 61158 part 2, suitable for 9-pin D-Sub (IP20) and M12 (IP67) connectors. Suitable for indoor, outdoor application in cable tray, conduit for fixed installation. Not suitable for direct burial.

CONSTRUCTION:

Conductor	Solid plain copper, 22AWG/ 0.34 mm ² .
Insulation	Cellular polyethylene.
Pair colour code	Green & Red.
Shielding	0.025 mm aluminium/polyester backed tape in continuous contact with a tinned copper drain wire 22 AWG (7strand) and tinned copper braid.
Outer Jacket	Extruded Violet colour PVC.
Printing Legend	MESC FIELDBUS CABLE IEC 61158-2 RS 485 PROFIBUS DP 1PR 22AWG 300 V 75C SUN RES OIL RES YEAR LENGTH MARKING

TECHNICAL DATA:

Flame retardance	IEC60332-3-24
Halogen acid gas	≤ 17% (IEC 60754-1)
Limiting Oxygen index (outer sheath)	≥ 29% (ASTM D2843)
UV /Sunlight resistance (outer sheath)	Passes (UL 1581)
Temperature Range	- 5°C to 50°C (During installation) - 30°C to 75°C (During Operation)
Voltage Rating	300 Volts
Conductor Resistance (Loop)	Max. 110 Ω/Km at 20°C
Shield Resistance	Nominal 12 Ω/Km at 20°C
Mutual Capacitance (at 1KHz)	30nF/Km Maximum
Attenuation at 0.25/0.625/1.25/3.125/16 MHz	Nominal 6/9/12/18/40 dB/km
Impedance	150 ±15 Ω
Voltage Test	1500 V

DIMENSION AND WEIGHT DETAIL:

SL/NO.	MESC Code	Size	Strands x Diameter	Outer Jacket Thickness	Approx. Outer Jacket O.D.	Approx. Weight
			No. x mm	mm	mm	Kg/Km
16	1863-01P22AWG-U2VT8-30	1 Pair x 22 AWG	1 X 0.65	0.8	8.0	65

ميسك
M E S C