

M E S C

Middle East Specialized Cable Co.

CO-AXIAL RG-213/U, MIL-C-17G 30V 60°C



Packing length and MESC CODE	Approx. Weight kg/km	Conductor				Insulation		Shield	Jacket		Nominal impedance	Nominal Capacitance	Nominal velocity Of propagation	Nominal Attenuation	
		Material	SIZE AWG	Strands X diameter No. x mm	Norm. D.C. Res. at 20° C ohm/Km	Material	Diameter mm	Material & coverage Nom. shield resistance	Material	Diameter mm	ohm	pF/m	%	MHZ	db / 100m
1000 M in Drum 2212-01CRG213-U1BK8-00	166	Bare Copper	13	7 x 0.76	5.6	PE	7.25	Bare Copper Braid 96% Coverage 3.9 Ω/Km	PVC BLACK 90°C	10.3	50	101.1	66	1	0.6
														10	2.0
														50	4.9
														100	6.9
														200	9.8
														400	15.7
														700	21.3
														900	24.9
1000	26.9														
PRINTING TEXT		CO-AXIAL CABLE RG-213 50 OHM MESC YEAR													

LEGEND:	
BC	⇨ Bare Wire
TC	⇨ Tinned Copper
CUWLD	⇨ Copper Covered Steel (copper weld)
PE	⇨ Solid Polyethylene
FPE	⇨ Cellular (Foam) Polyethylene
AL	⇨ Aluminum
AMT	⇨ Aluminum Mylar Tape
LSHF	⇨ Low Smoke Halogen Free