

M E S C

MIDDLE EAST SPECIALIZED CABLE CO.
CO-AXIAL MATV CABLES

RG-11/U 75 Ohms



Packing length and MES C CODE	Approx. Weight kg/km	Conductor				Insulation		Shield	Jacket		Nominal Impedance.	Nominal Capacitance	Nom. vel Of prop.	Nominal Attenuation	
		Material	AWG	Strands X diameter No. x mm	Nom. D.C. Res. at 20° C ohm/Km	Material	Diameter. mm	Material & coverage Norm. shield resistance	Material	Diameter mm	ohm	pF/m	%	MHz	db / 100m
1000 meter in Drum 2833-01CRG11U-U3BK8-00	73	CU WELD	14	1 x 1.63	41.4	FPE	7.25	100% AMT and 40% Al wire braid 17.4 Ω / Km	PVC BLACK 90°C	10.3	75	53.1	82	1	1.0
														10	2.0
														50	3.0
														100	3.9
														200	5.6
														400	7.9
														700	11.5
														900	12.5
														1000	13.1
Printing Text	CO-AXIAL CABLE MATV RG-11U TYPE 75 OHM MES C YEAR														

LEGEND:	
BC	⇒ Bare Wire
TC	⇒ Tinned Copper
CUWLD	⇒ Copper Covered Steel (copper weld)
PE	⇒ Solid Polyethylene
FPE	⇒ Cellular (Foam) Polyethylene
AL	⇒ Aluminum
AMT	⇒ Aluminum Mylar Tape
PVC	⇒ Polyvinyl Chloride